



Mounted Transom Patch, External Corner Installation

Product # 701RPF007170

DESCRIPTION

Suitable for corner top pivot installation.

Mounted transom patch for installation on glass panels, creating the glass closure for the external corner. Can be used with several kinds of adapters, according to the frameless glass panel layout to be created. Suitable for various thicknesses of glass.

ADVANTAGES AND BENEFITS

Can create an all-glass design, as seen in offices or other glass structures in commercial zones. Its L-shape can hold in place two glass panels and a glass door for an opening and closing system.

REQUIRED PRODUCTS

Requires the following products

Sales unit



Door Stop for Top Transom Patch
 Product # 701RPF1306SD

TECHNICAL SPECIFICATIONS

Product #	701RPF007170
Finish	Brushed Stainless Steel
Glass Thickness	13/32 to 15/32 in*
Length	8 19/32 in*
Material	Stainless Steel: 304
Height	4 3/16 in*

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

APPLICATION

Installed on the glass to support a crosspiece from the lateral glass partition. By using the correct pivot, the door can open one-way or two-ways.

IMPORTANT INFORMATION

For safety purposes, use tempered glass. The glass must be shaped according to the section plane provided in the box. Always set the product in a suitable material. Never exceed the load or maximum size recommended by the manufacturer. Make sure to order the hardware before starting the works. This illustration is provided for visual reference only. Actual product may differ from the illustration. The manufacturer reserves the right to change the product and information without notice. Always use the instructions inside the package. Drawings and technical documents contain examples of hardware from different manufacturers. The customer may in no case make a claim following the use of these documents. The Company disclaims any responsibility for the structural details related to a construction or project. Installation must be done by qualified personnel.

DISCLAIMER

The preceding information as well as any technical recommendation given in writing or verbally, whether based on tests or not, is provided to the best of our knowledge. These recommendations are non-binding and do not diminish your responsibility for determining their correctness, as well as the suitability of the product for your particular purpose. The application, use or processing of our products, as well as the execution of projects based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

PRODUCT PHOTOS

