



## Tremco® 830

**Product #** D030108

### DESCRIPTION

#### Thermoplastic, Elastomeric Glass and Siding Sealant

Tremco 830 is a one-part, thermoplastic elastomer that provides a high-performance, flexible seal in glazing and siding applications.  
Not for use in the United States.

### ADVANTAGES AND BENEFITS

- Fast skinning, fast cure through. - Easy gunning. - Excellent weather and UV resistance. - Can be painted with latex paint

### TECHNICAL SPECIFICATIONS

<b>Product #</b>	D030108
<b>Brand</b>	Tremco
<b>Finish</b>	Transparent Clear
<b>Product Type</b>	Thermoplastic Elastomere
<b>Ideal Use</b>	Aluminum Windows, Wood Windows, Vinyl (PVC) Windows, Exterior Trim & Siding, Outside
<b>Base</b>	Elastomeric Polymer
<b>Optimal adherence to</b>	Concrete, Non-oiled Wood, Brick, Aluminum, Vinyl, Masonry
<b>Tooling Time</b>	Immediately tool the sealant
<b>Volume</b>	10.1 oz*
<b>Properties</b>	Paintable
<b>Packaging Specifications</b>	Cardboard Cartridge

#### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

### APPLICATION

Basic Uses: - Can be used in glazing applications for face bedding and cap beads and sealing miter joints in window profiles. - Can be used for siding applications with sill trim, flashings, fascia, J-trim, F-channel and crown molding. - Can also be used for sealing perimeters of wood, PVC and aluminum residential windows and doors.

### IMPORTANT INFORMATION

- Not for use in the United States. - Do not apply Tremco 830 over damp or contaminated surfaces. - Do not use in contact with polystyrene, insulated glass seals or laminated glass. - Always utilize the accompanying MSDS for information on Personal Protective - Equipment (PPE) and health hazard

---

## PRODUCT PHOTOS

