



## Stainless Steel Glue Activator

**Product #** HR19133100001

### DESCRIPTION

#### Low temperature curing

Primer: Loctite 7649 Surface Treatment - Activator, solvent based

### ADVANTAGES AND BENEFITS

Increases the cure speed of adhesives without significant loss of joint strength. Ideal for applications on passive metals or inert surfaces, such as stainless steel and glass

## REQUIRED PRODUCTS!

Requires the following products

**Sales unit**



### Stainless Steel Glue

Product # HR19133100000

AND



### Stainless Steel Glue

Product # HR19133100000

## TECHNICAL SPECIFICATIONS

<b>Product #</b>	HR19133100001
<b>Base</b>	Acetone
<b>Weight</b>	0.88 oz
<b>VOC Concentration (EPA Method 24)</b>	11.7 grams per liter
<b>Standards and Certifications</b>	CFIA, NSF/ANSI 61, NSF P1
<b>Open Time</b>	75 seconds
<b>Finish/Color</b>	Green
<b>Brand</b>	Loctite®

---

## APPLICATION

Applicable materials for glue: most metals, glass. Resistance: weather, solvent. Recommended when the application temperature is below 15°C.

## IMPORTANT INFORMATION

Additonal standards et certifications: -for new designs: ASTM-D5363 -for existing designs: MIL-S-22473E

## PRODUCT PHOTOS

