



## 180° Connector for Glass, with Rounded Ends

**Product #** HRGCR6534180170

### DESCRIPTION

**Fixed straight connection for glass mounting**

Fixed bracket designed to connect two glass panels in a continuous line

### ADVANTAGES AND BENEFITS

Increases glass stability when used with the safety lock pin. Provides a clear and open view free of visual obstructions. Suitable for various glass types and thicknesses

## TECHNICAL SPECIFICATIONS

<b>Product #</b>	HRGCR6534180170
<b>Type of Mounting</b>	Glass Mount
<b>Safety Glass Thickness</b>	15/32 in*
<b>Finish</b>	Stainless Steel
<b>Height</b>	1 25/32 in*
<b>Width</b>	1 3/16 in*
<b>Length</b>	4 3/16 in*
<b>Material</b>	Stainless Steel 316
<b>Glass Drilling</b>	Not Required
<b>Recommended Location Usage</b>	Interior, Exterior
<b>Mounting Side</b>	Reversible
<b>Category</b>	Glass Connectors
<b>Milling Diameter</b>	13/32 in*

### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

## APPLICATION

Easily matches glass railing projects such as staircases and balustrades.

## INCLUDED PRODUCT(S)

Stainless steel safety lock pins Gaskets for 12mm glass Screw caps

---

## IMPORTANT INFORMATION

For safety purposes, use tempered glass. Glass drilling is required when using the safety lock pin. This illustration is provided for visual reference only. Actual product may vary. The manufacturer reserves the right to change product and information without notice. Always follow the instructions inside the package. Installation must always be done by qualified personnel.

## DISCLAIMER

The above information, as well as any written or verbal technical advice, whether or not based on tests, is provided to the best of our knowledge. These tips are not binding, and it is your responsibility to personally verify their accuracy. It is also your responsibility to check the suitability of the product for the intended purpose. The application, use and transformation of our products, as well as projects carried out following our technical advice, are beyond our control and are your sole responsibility. The sale of our products is subject to the general conditions of sale and delivery in force. Please note that Richelieu will refuse any return or claim for an unpackaged product.

## PRODUCT PHOTOS

