



Connector Elbow for Handrail, Left Hand

Product # SSEBLNDLEFT

DESCRIPTION

90° Angle, Adjustable from 0° to 70°

Connector elbow for tube handrails can be adjusted. Perfect for custom railings.

ADVANTAGES AND BENEFITS

Allows flexibility in round handrails given its adjustable elbow. Works well with several handrail applications, especially for rails and risers in glass, cable and tubing.

REQUIRED PRODUCTS

Requires the following products

Sales unit



Stainless Steel Glue Activator Product # HR19133100001





Stainless Steel Glue Product # HR19133100000



TECHNICAL SPECIFICATIONS

Product #	SSEBLNDLEFT
Handrail Type	Round Tubing
Finish	Stainless Steel
Recommended Location Usage	Interior, Exterior
Mounting Side	Left Side
Material	Stainless Steel 316
Handrail Size	ø 42.4 mm (1 27/32")
Curvature angle	0° to 70°, 110° to 180°, 90°
Thickness	3/32 in*
Category	Connectors

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, <u>click here</u>.

APPLICATION

Insert the connector in one of the ends of the round tube making up the handrail and adjust it to the desired angle. Adhesive netting provides better stability for the connector after installation.

IMPORTANT INFORMATION

The use of power tools during installation may damage the decorative hardware. Always set the product in a suitable material. Never use a spray lubricant on this product. Maintenance: clean with a soft cloth and non-abrasive soap or ammonia. This illustration is provided for visual reference only. Actual product may differ from the illustration. The manufacturer reserves the right to change product and information without notice. Always use the instructions inside the package. Drawings and technical documents contain examples of hardware from different manufacturers. The customer can in no case make a claim following the use of these documents. The Company waives any responsibility for the structural details related to a construction or project. Installation must be done by qualified personnel.

DISCLAIMER

The preceding information as well as any technical recommendation given in writing, verbally or based on tests is provided to the best of our knowledge. However, recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use or processing of our products as well as the production of products based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.



PRODUCT PHOTOS

