



Pivot Hinge for Glass Door Recessed Within Furniture or Cabinet

Length

Width

Height

Thumb Screws

Finish



Black



Chrome



Satin Chrome



Satin Nickel

Packaging format

DESCRIPTION

No drilling of glass

AVAILABLE PRODUCTS

Product #	Length	Width	Height	Thumb Screws	Finish	Packaging format
2001140	1 9/16 in*	15/32 in*	1/2 in*	Metal	Chrome	Pair
BP2001140	1 9/16 in*	15/32 in*	1/2 in*	Metal	Chrome	Bag of 2 units
576FBR	1 9/16 in*	15/32 in*	1/2 in*	Plastic	Black	Blister of 2 units
480612145	1 5/8 in*	7/16 in*	19/32 in*	Plastic	Satin Chrome	Pair
480612185	1 5/8 in*	7/16 in*	19/32 in*	Plastic	Satin Nickel	Pair
200190	1 5/8 in*	15/32 in*	19/32 in*	Plastic	Black	Pair
BP200190	1 5/8 in*	15/32 in*	19/32 in*	Plastic	Black	Pair

TECHNICAL SPECIFICATIONS

Material	Steel
Thickness of Glass	3/16 to 1/4 in*
Load Capacity	Max. 5.51 lb*
Dimensions to subtract from the height	3/8 in
Dimensions to subtract from the width	3/32 in
Height of Door to Respect	Max. 31 1/2 in*
Width of Door to Respect	Max. 19 5/8 in*
Screw/Nail	Included

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

IMPORTANT INFORMATION

Please refer to technical drawing for detailed measurements. Note: The dimensions indicated above are guidelines that provide satisfactory results in most cases. For more precise installations, your own calculations can be made when you have hinges and cabinets in hand.

APPLICATION

Glass Preparation: - Glass Height: Opening Minus 3/8". - Single Door Width: Opening Minus 3/32". - Double Door Width: Opening Minus 5/64". Press fit bushing.

INCLUDED PRODUCT(S)

Screws are included.

PRODUCT PHOTOS

