



Concealed "T" Standard - No. 704 and 705

Length

72 in

96 in

"T" Height

11/16 in

13/16 in

DESCRIPTION

- 1/8" thick steel
- On center dimension from countersunk screw hole to countersunk screw hole is 6" staggered side-to-side
- Requires screw #10
- Loose fixtures and perimeter

AVAILABLE PRODUCTS

Product #	Length	"T" Height
704062G	72 in	11/16 in
705062G	72 in	13/16 in
704082G	96 in	11/16 in
705082G	96 in	13/16 in

TECHNICAL SPECIFICATIONS

Mounting	Concealed
Gauge	14
Width	1 1/2 in*
Slot Width	3/16 in
Slot Adjustment	2 in
Material	Steel
Color/Finish	Zinc

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

APPLICATION

INSTALLATION All wall mounted standards should be installed with the stamp right-side up, the widest margin at the bottom and typically a half slot at the top. Before mounting to the wall, line up each standard using the bottom of each bottom slot as the guide. Once aligned, make sure to fasten to a secure wall stud (or equivalent) using appropriate screws. Make sure to utilize each screw hole. All recessed/concealed "T"-standards should be mounted right-side up as shown by the "top" stamp. Before mounting, line up each standard using the bottom of each bottom slot as the guide. Once aligned, make sure to fasten to a secure wall stud (or equivalent blocking) using appropriate screws (see Drawing A). Make sure to utilize each screw hole. Please note that a minimum 3/it by 1/s" notch is required in the stud or blocking to allow installation of brackets.

PRODUCT PHOTOS





