



90° Glass-to-Wall Offset Clamp - Square

Finish

Bright Brushed Matte Black
Polished Nickel
Chrome

DESCRIPTION

Fixation: glass-to-wall

These clamps attach directly to the wall, ceiling or floor to hold vertical glass panels in place.

Allows juxtaposing the glass panel perpendicular to the wall at a 90° angle

ADVANTAGES AND BENEFITS

Its L-shaped plate makes it possible to juxtapose the glass panel closer to the wall. Can be used with many thicknesses of tempered glass. Ideal for frameless shower enclosures

AVAILABLE PRODUCTS

Product #	Finish
SC1SQ90OW140	Bright Polished Chrome
SC1SQ90OW195	Brushed Nickel
SC1SQ90OW900	Matte Black

TECHNICAL SPECIFICATIONS

Application	Fixed Screen, Corner Shower, Neo-Angle Shower, Door and Panel
Load Capacity	Max. 77.2 lb*
Milling Diameter	5/8 to 3/4 in*
Glass Thickness	13/32 to 15/32 in*
Height	2 in*
Width	2 in*
Length	2 in*
Material	Solid Brass
Style	Square

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, <u>click here</u>.

APPLICATION

Glass drilling required for installation.



IMPORTANT INFORMATION

For safety purposes, use tempered glass. The use of power tools during installation may damage the hinges and decorative hardware. The glass must be shaped according to the section plan provided in the box. Always set the product in a suitable material. Never exceed the load or maximum size recommended by the manufacturer. Never use a spray lubricant on this product. Maintenance: clean with a soft cloth and non-abrasive soap or ammonia. This illustration is provided for visual reference only. Actual product may differ from the illustration. Order hardware before starting the job. The manufacturer reserves the right to change product and information without notice. Always use the instructions inside the package. Drawings and technical documents contain examples of hardware from different manufacturers. The customer may in no case make a claim following the use of these documents. The Company disclaims any responsibility for the structural details related to a construction or project. Installation must be done by qualified personnel. Always make sure that the product is properly set to the support material using suitable fixings. Never exceed the load or maximum size recommended by the manufacturer. Never use a spray lubricant on this product.

DISCLAIMER

The preceding information as well as any technical recommendation given in writing, verbally or based on tests is provided to the best of our knowledge. However, recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use or processing of our products as well as the production of products based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.



PRODUCT PHOTOS







