




Round Glass Glamp for Flat Surface Mounting, Adjustable

Finish



Safety Glass Thickness

3/16 to 13/32
in*

3/16 to 15/32
in*

Height

2 1/8 in

2 11/64 in

Width

2 1/8 in

2 3/16 in

Material



Stainless
Steel 304



Zinc

Thickness

63/64 in

1 in

Packaging format

Box

Bag of 2 units

DESCRIPTION

Adjustable with two set screws

Adjustable glass clip with two set screws on the side to facilitate installations.

AVAILABLE PRODUCTS

Product #	Finish	Safety Glass Thickness	Height	Width	Material	Thickness	Packaging format
GMGC397BLK	Black	3/16 to 15/32 in*	2 1/8 in	2 3/16 in	Zinc	1 in	Box
GMGC397GM	Black Nickel	3/16 to 15/32 in*	2 1/8 in	2 3/16 in	Zinc	1 in	Box
GMGC397BN	Brushed Nickel	3/16 to 15/32 in*	2 1/8 in	2 3/16 in	Zinc	1 in	Box
GMGC397C	Chrome	3/16 to 15/32 in*	2 1/8 in	2 3/16 in	Zinc	1 in	Box
BP3100174	Satin Chrome	3/16 to 13/32 in*	2 11/64 in	2 1/8 in	Zinc	63/64 in	Bag of 2 units
GMGC397SC	Satin Chrome	3/16 to 15/32 in*	2 1/8 in	2 3/16 in	Zinc	1 in	Box
BP3100195	Satin Nickel	3/16 to 13/32 in*	2 11/64 in	2 1/8 in	Zinc	63/64 in	Bag of 2 units
GMGC397BS	Stainless Steel	3/16 to 15/32 in*	2 1/8 in	2 3/16 in	Stainless Steel 304	1 in	Box

TECHNICAL SPECIFICATIONS

Recommended Location Usage	Interior
Glass Drilling	Not Required
Baluster Post Type	Square Tube

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

APPLICATION

For mounting on round posts, a radius base plate can be added during installation. See individual finishes for availability.

INCLUDED PRODUCT(S)

1 pair of sealing gaskets included

IMPORTANT INFORMATION

Recommended glass deduction is roughly 7/8" For safety purposes, use tempered glass. The use of power tools during installation may damage the hinges and decorative hardware. The glass must be shaped according to the section plane provided in the box. Always set the product in a suitable material. Never exceed the load or maximum size recommended by the manufacturer. Never use a spray lubricant on this product. Maintenance: clean with a soft cloth and non-abrasive soap or ammonia. This illustration is provided for visual reference only. Actual product may differ from the illustration. Order hardware before starting the job. The manufacturer reserves the right to change product and information without notice. Always use the instructions inside the package. Drawings and technical documents contain examples of hardware from different manufacturers. The customer may in no case make a claim following the use of these documents. The Company disclaims any responsibility for the structural details related to a construction or project. Installation must be done by qualified personnel. Always make sure that the product is properly installed using suitable fixings to the support material. Never exceed the load or maximum size recommended by the manufacturer. Never use a spray lubricant on this product.

DISCLAIMER

The preceding information as well as any technical recommendation given in writing, verbally or based on tests is provided to the best of our knowledge. However, recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use or processing of our products as well as the production of products based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

PRODUCT PHOTOS



