



## Curved End Cap

### Recommended Location Usage

Exterior

Interior

 Interior /  
Exterior

### Material


 Stainless  
Steel 304

 Stainless  
Steel 316

### Handrail Size

 ø 38.1 mm (1  
1/2")

 ø 42.4 mm (1  
27/32")

 ø 50.8 mm  
(2")

### Thickness

1/16 in\*

3/32 in\*

## DESCRIPTION

### Radius Wall Return

This return will give an elegant look to a staircase handrail.

## ADVANTAGES AND BENEFITS

Suitable for various commercial applications, such as round handrails for glass, cable or rod railings, handrails and footrails for bar counters.

## AVAILABLE PRODUCTS

Product #	Recommended Location Usage	Material	Handrail Size	Thickness
<b>HR18620438170</b>	Exterior	Stainless Steel 316	ø 38.1 mm (1 1/2")	3/32 in*
<b>HR18420450170</b>	Interior	Stainless Steel 304	ø 50.8 mm (2")	3/32 in*
<b>SSEB1320116S</b>	Interior / Exterior	Stainless Steel 316	ø 42.4 mm (1 27/32")	3/32 in*
<b>SSEB1350316S</b>	Interior / Exterior	Stainless Steel 316	ø 50.8 mm (2")	1/16 in*

---

## TECHNICAL SPECIFICATIONS

Handrail Type	Round Tubing
Finish	Stainless Steel
Category	Finials

### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

## APPLICATION

Finial to be inserted at one end of a round tube forming a handrail or a footrest

## IMPORTANT INFORMATION

Always set the product in a suitable material. Maintenance: clean with a soft cloth and non-abrasive soap or ammonia. This illustration is provided for visual reference only. Actual product may differ from the illustration. Order hardware before starting the job. The manufacturer reserves the right to change product and information without notice. Drawings and technical documents contain examples of hardware from different manufacturers. The customer may in no case make a claim following the use of these documents. The Company disclaims any responsibility for the structural details related to a construction or project. Installation must be done by qualified personnel. Always make sure that the product is properly installed using suitable fixings to the support material. Never exceed the load or maximum size recommended by the manufacturer. Never use a spray lubricant on this product.

## DISCLAIMER

The preceding information, as well as any technical recommendation given in writing or verbally, whether based on tests or not, is provided to the best of our knowledge. Recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use or processing of our products, as well as the execution of projects based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

## PRODUCT PHOTOS

