



## Adjustable Angle Connector from 0° to 90°

### DESCRIPTION

#### Adjustable flush angle (0° to 90°)

Square 90° connectors for square handrails.  
 These connectors provide a smooth finish to your handrails.

### ADVANTAGES AND BENEFITS

Articulated elbow making it easier to adjust the angle of the handrail when used in a staircase application. Allows angle adjustment from 0° to 90°. Easy to use, insert and glue the fitting inside each end of the square handrail

## AVAILABLE PRODUCTS

Product #

**SSZE1404016S**

## TECHNICAL SPECIFICATIONS

Handrail Type	Flat Tubing
Finish	Satin Stainless Steel
Recommended Location Usage	Interior, Exterior
Material	Stainless Steel 316
Handrail Size	40 mm x 40 mm (1 9/16" x 1 9/16")
Baluster Post Size	40 mm x 40 mm (1 9/16" x 1 9/16")
Type of Mounting	Post Mount
Thickness	3/32 in*
Category	Connectors
Baluster Post Type	Square Tube

### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

## APPLICATION

Connects two square tubes creating the corner connection for the handrail Ideal for architectural projects such as staircases and glass, cable or rod balustrades A glue strand during assembly helps to solidify and better secure the connection between the components.

---

## IMPORTANT INFORMATION

Always set the product in a suitable material. Never exceed the load or maximum size recommended by the manufacturer. Never use a spray lubricant on this product. Maintenance: clean with a soft cloth and non-abrasive soap or ammonia. This illustration is provided for visual reference only. Actual product may differ from the illustration. Order hardware before starting the job. The manufacturer reserves the right to change product and information without notice. Always use the instructions inside the package. Drawings and technical documents contain examples of hardware from different manufacturers. The customer may in no case make a claim following the use of these documents. The Company disclaims any responsibility for the structural details related to a construction or project. Installation must be done by qualified personnel. Always make sure that the product is properly installed using suitable fixings to the support material. Never exceed the load or maximum size recommended by the manufacturer. Never use a spray lubricant on this product.

## DISCLAIMER

The preceding information as well as any technical recommendation given in writing, verbally or based on tests is provided to the best of our knowledge. However, recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use or processing of our products as well as the production of products based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

## PRODUCT PHOTOS

---

