



# 1 3/16" (30 mm) Square Tubular Pull Handles with Wood Insert for Back-to-Back Mounting

# **Center to Center Drilling (Spacing)**

24 in	36 in

## Height

24 1/2 in	36 1/2 in

#### **DESCRIPTION**

#### Wooden handle

This handle can be used on hinged or sliding doors. Its square design will add a personalized modern touch to your commercial development projects.

### **ADVANTAGES AND BENEFITS**

The black wooden handle provides a refined and versatile feature that is suitable for all environments. The handle can be installed either on a glass or wood door.

#### **AVAILABLE PRODUCTS**

Product #	Center to Center Drilling (Spacing)	Height
70524SQ30BW170	24 in	24 1/2 in
70536SQ30BW170	36 in	36 1/2 in



#### **TECHNICAL SPECIFICATIONS**

Color/Finish	Black, Stainless Steel
Glass Thickness	5/16 to 15/32 in*
Usage	Sliding Door, Hinge Door
Door Type	Glass, Wood, Architectural
Function	Back-to-Back Pull Handle
Width	1 3/16 in*
Projection	2 3/4 in*
Material	Stainless Steel 304, Wood
Туре	Square
Thickness	1 3/16 in*
Milling Diameter	15/32 in*
Brand	Richelieu Glass Products
Door Thickness	1 3/8 to 1 31/32 in*
Screw/Nail	Included, M8

#### **Disclaimer**

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, <u>click here</u>.

#### APPLICATION

Ideal for offices, conference rooms, exhibition halls and shopping centers

# INCLUDED PRODUCT(S)

Installation hardware for mounting on glass and wood included.

#### IMPORTANT INFORMATION

For safety purposes, use tempered glass. Glass drilling is required for use. When mounting on wood doors, a thickness of 45 mm (1-49/64 mm) must be respected. This illustration is provided for visual reference only. Actual product may vary. Order hardware before starting the job. The manufacturer reserves the right to change product and information without notice. Always follow the instructions inside the package. Drawings and technical documents contain examples of hardware from different manufacturers. The customer may not in any case make a claim following the use of these documents. The Company disclaims any responsibility for the structural details related to a construction or project. Installation must always be done by qualified personnel.

#### DISCLAIMER

The preceding information, as well as any technical recommendation given in writing or verbally, whether based on tests or not, is provided to the best of our knowledge. Recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use or processing of our products, as well as the execution of projects based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.



# PRODUCT PHOTOS

