



## Back-to-Back Square Ladder Handle with Square Mounting Rods

### Color/Finish



### Center to Center Drilling (Spacing)

12 in

24 in

36 in

48 in

### Height

24 in

36 in

48 in

60 in

## AVAILABLE PRODUCTS

Product #	Color/Finish	Center to Center Drilling (Spacing)	Height
701DH153224169	Black Stainless Steel	12 in	24 in
701DH153236169	Black Stainless Steel	24 in	36 in
701DH153248169	Black Stainless Steel	36 in	48 in
701DH153260169	Black Stainless Steel	48 in	60 in
701DH153224170	Stainless Steel	12 in	24 in
701DH153236170	Stainless Steel	24 in	36 in
701DH153248170	Stainless Steel	36 in	48 in
701DH153260170	Stainless Steel	48 in	60 in
701DH153224171	Chrome / Polished Stainless Steel	12 in	24 in
701DH153236171	Chrome / Polished Stainless Steel	24 in	36 in
701DH153260171	Chrome / Polished Stainless Steel	48 in	60 in

---

## TECHNICAL SPECIFICATIONS

<b>Door Type</b>	Glass, Wood
<b>Glass Thickness</b>	5/16 to 15/32 in*
<b>Door Thickness</b>	1 3/8 to 1 31/32 in*
<b>Thickness</b>	1 1/4 in*
<b>Width</b>	1 1/4 in*
<b>Projection</b>	2 27/32 in*
<b>Material</b>	Stainless Steel 316
<b>Type</b>	Square
<b>Usage</b>	Sliding Door, Hinge Door, Commercial Door
<b>Milling Diameter</b>	9/16 in*
<b>Function</b>	Back-to-Back Pull Handle
<b>Screw/Nail</b>	Included, M8

### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

## IMPORTANT INFORMATION

Picture for visual reference only: actual product may vary from that shown in photo. Be sure to order hardware before beginning fabrication or installation work. Always use the instructions inside the packaging provided by the manufacturer, as the manufacturer reserves the right to make technical changes or modify information without prior notice. All technical drawings and documents contain examples for the assembly of different suppliers' hardware. The customer cannot make any claims based on the use of these documents. No responsibility is assumed for design details relating to a construction or project. At all times, execution and installation must be undertaken by qualified persons. Always be sure to install the product correctly using the appropriate fixation for your material. Never exceed the maximum weight or the maximum dimensions recommended by the manufacturer.

## DISCLAIMER

The preceding information as well as any technical recommendations given in writing, verbally or based on tests are provided to the best of our knowledge. However, they are non-binding recommendations only and do not affect your responsibility to determine the correctness of given recommendations and suitability of the product for your particular purposes. The application, use or processing of our products as well as the production of products based on our technical recommendations are beyond our control and therefore fall exclusively in your area of responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

## PRODUCT PHOTOS

---

