



I-Box 02 Frameless

Finish

Matte Black

 Polished
chrome

DESCRIPTION

Soft-close sliding system for a corner glass shower

Equipped with "SOFTY", an innovative and patented soft-close system. As opposed to traditional soft-close systems, minimal force is needed to release the damper and open/close the door. With no latch or release points, the motion of the door is smooth, constant, and silent.

Thanks to the combination of the Softy system and a patented profile applied to the thickness of the glass, complete sealing of the system can be achieved, resulting in no annoying leaks from the shower cabin.

The self-adjusting floor guide integrated into the floor guard automatically adjusts to the thickness of the glass, minimizing door oscillations and vibrations, and eliminating noise caused by the glass movement during sliding. The minimum distance between the sliding door and the fixed panel is 11 mm.

ADVANTAGES AND BENEFITS

Exceptional ease of movement and silence. Reduced distance between the sliding door and fixed glass. Minimum door width of 500 mm. Patented, self-regulating floor guide integrated into the floor barrier, Watertight door closing. Very quick assembly and adjustment. Successfully tested with 200,000 opening and closing cycles. Minimal design thanks to the reduced size and the absence of mechanical parts on sight.

AVAILABLE PRODUCTS

Product #	Finish
755IBOX02FL900	Matte Black
755IBOX02FL140	Polished chrome

TECHNICAL SPECIFICATIONS

Load Capacity	110 lb*
Glass Thickness	1/4 to 5/16 in*
Recommended Door Height	90 1/2 in*
Max. Fixed Panel Height	90 1/2 in*
Recommended Door Width	37 in*
Enclosure Width	Max. 78 3/4 in*
Recommended Fixed Panel Width	41 3/8 in*

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

IMPORTANT INFORMATION

This illustration is provided for visual reference only. Actual product may vary. Order hardware before starting the job. Always follow the instructions inside the package. The manufacturer reserves the right to change product and information without notice. Installation must always be done by qualified personnel. Make sure that the product is properly installed using suitable fixtures on the support material. Never exceed the maximum load or size recommended by the manufacturer. The Company disclaims any responsibility for the structural details related to a construction or project.

DISCLAIMER

The preceding information, as well as any technical recommendation given in writing or verbally, whether based on tests or not, is provided to the best of our knowledge. Recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use or processing of our products, as well as the execution of projects based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

PRODUCT PHOTOS

